



Product Service

Attestation of Conformity

No. E8A 122967 0007 Rev. 01

Holder of Attestation: **Zhejiang Bison Machinery Co.,Ltd**

Room 102, Building 1, No.1988-1, Haichang Road
Sanjia Subdistrict, Taizhou Bay District
318000 Taizhou, Zhejiang
PEOPLE'S REPUBLIC OF CHINA

Name of Object: **Generator/Transformer/Accumulator,
portable
Inverter Gasoline Engine Generator**

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 4840324352601

Date, 2025-12-11

(Jun Bao)

Page 1 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

Attestation of Conformity

No. E8A 122967 0007 Rev. 01

Model(s): BS1500i, BS1500i-#,
 BS3750i, BS3750i-#,
 BS4500i, BS4500i-#
 "#" can be blank, a-z, A-Z or 1-9

Description of Object:

Rated AC output voltage: 230V~50Hz
 For Model: BS1500i ,BS1500i-#("#" can be blank, a-z, A-Z or 1-9)
 Rated AC output power: 0,9kW(COP);
 Max. AC output power: 1,0kW S2 5min;
 Rated DC output power: USB: 5,0V 1,0A/2,1A
 For Model: BS3750i ,BS3750i-#("#" can be blank, a-z, A-Z or 1-9)
 Rated AC output power: 3,5kW(COP)
 Max. AC output power: 3,7kW S2 5min
 Rated DC output power: DC12V/5A
 USB: 5,0V 1,0A/2,1A
 For Model: BS4500i ,BS4500i-#("#" can be blank, a-z, A-Z or 1-9)
 Rated AC output power: 3,8kW(COP)
 Max. AC output power: 4.0kW S2 5min
 Rated DC output power: DC12V/5A
 USB: 5,0V 1,0A/2,1A

Tested according to: EN 55012:2007/A1:2009
 EN IEC 61000-6-1:2019